



### **CHECK RIDGE TO CENTRE GUTTER MEASUREMENT**

**IF YOU NEED TO MAKE ADJUSTMENT TO ROOF LENGTH, ADD OR OMIT "H", "G" OR "F" COURSES. MAKE CERTAIN YOU FINISH WITH ONE "K" COURSE. IF YOU MAKE ANY ADJUSTMENTS PLEASE LET US KNOW AS YOU MAY RUN OUT OF SLATES**

### **ALIGNMENT OF UNDER-EAVE SLATE**

**THE LENGTH OF "S" & "Q" SLATES CAN VARY SLIGHTLY AND THE EAVES "TILT" CAN VARY. IT IS BEST TO NAIL UNDER-EAVE BATTEN USING UNDER-EAVE SLATE TO CHECK ALIGNMENT**

### **NAIL TOP BATTENS ON EDGE**

**THE BATTENS FOR "J" & "K" ARE VERY CLOSE TOGETHER WHICH CAUSES A PROBLEM FITTING THE SLATES. BEST METHOD IS TO USE 25 X 38MM BATTEN ON EDGE. THIS ALLOWS ENOUGH ROOM FOR THE NIB AND RAISES THE SLATE SLIGHTLY TO OVERCOME ANY ROCKING**

### **THERE ARE A LIMITED NUMBER OF WIDE SLATES**

**IT IS VERY IMPORTANT TO SAVE THEM FOR CUTTING HIPS AND VALLEYS. THE KEY IS TO GET THE BOND GOING SO THAT THE SLATES CAN BE LAID RATHER LIKE PLAIN TILES, USING FEW WIDE SLATES IN THE BODY OF THE ROOF.**

### **MIX THE COLOURS**

**THERE SHOULD BE A VARIETY OF COLOUR SHADES FROM FAIRLY DARK TO FAIRLY LIGHT - PLEASE BE CERTAIN TO DISTRIBUTE THESE SO NO BANDING OCCURS. IF THERE IS NOT A SUITABLE MIX OF COLOURS, CALL AS SOON AS POSSIBLE**

### **DRESSING THE VERGE SLATES**

**THE EASIEST WAY TO DRESS THE VERGE SLATES IS TO GET A WIDER SLATE AND KNOCK ONE OF THE NIBS OFF. IF THEY ARE CUT THEN THE AGGREGATE MAY BE VISIBLE.**

### **AN EXCESS OF TILES IS ALWAYS SUPPLIED**

**THESE EXTRA TILES HAVE NOT BEEN INVOICED FOR AND SHOULD BE STACKED NEATLY IN THE CRATES FOR RETURN.**

**IF YOU HAVE ANY QUESTIONS, CALL TOM OR RICHARD**

**01993 778 557 / 07888 778 557 / OFFICE@CARDINALSLATES.CO.UK**